

Configurable OEM Oxygen Transmitter, 2-wire loop



2-Wire Loop Powered Configuration
Well Suited for OEM Installations
Precision Fuel Cell Oxygen Sensor Technology
Trace or Percent Configuration
Measure Oxygen from 0.01ppm to 100%
Updated Microprocessor Based Design
Cost Effective, Compact and Low Maintenance
Integrates seamlessly with PLC and DCS Systems



H3 Flow Throw
Sensor Housing



H1 KF-40
Sensor Housing



Oxygen Sensor

Applications:

- Inert Glove Box Systems
- Nitrogen and O2 PSA Generators
- Laboratories & Universities
- 3D Metal Printing Systems
- Air Separation Plants
& Many Others

Configurations:

User Selectable Ranges (Pre-Configured):
0 - 10ppm/100/1000ppm/1%/5%/10%/25%/100%
Digital Push Buttons to Perform Local Span Cal
Sensor Housings: H1 KF-40 or H3 Flow Through
Optional Display without Backlight
Many additional customized options available

Specifications:

Accuracy:	< 1% Full Scale Range*
Calibration:	2 - 3 months or as needed
Classification:	General Purpose
Dimensions (PCB):	3.25 x 2.00 inch
Display:	Optional
Temperature:	0 - 50 deg C
Temperature Compensation:	Integral
Output:	4 - 20mA
Sensor Housing:	Optional, H1 or H3
Flow Sensitivity:	0 - 5.0 SCFH
Sensor Type:	Precision Fuel Cell
Warranty:	12 Months Sensor
Warranty:	12 Months Electronics

*Accuracy at constant conditions

"Inquiry for Application Expertise"

Oxygen Transmitter:

The model EMD-482 oxygen transmitter combines a rugged electronic design with SSO2's precision oxygen sensors. The result is a highly reliable and cost effective compact design with easy-to-use user interface.

The transmitter comes with a variety of options, which makes it configurable for a large array of applications. These options include custom ranges from 0 - 10ppm through 0 - 100%, a local display, sensor housings for flow through applications and ambient monitoring, as well as a variety of oxygen sensors. See the below ordering guide for complete options.

This unit is configured as a 2-wire loop powered device and is ideal for integration with a PLC or DCS system. Output is non-isolated.

Oxygen Sensor Technology:

The oxygen sensor used in the EMD-482 is based on the galvanic electrochemical fuel cell principal. All oxygen sensors are manufactured in house by Southland Sensing Ltd. under a strict quality program.

The standard cells are unaffected by other background gases such as H₂, He or Hydrocarbons. The acidic cells work well when acid gases such as CO₂ or Natural Gas are present.

The sensors are self-contained and minimal maintenance is required - no need to clean electrodes or add electrolyte.

The SSO2 precision oxygen sensors offer excellent performance, accuracy and stability while maximizing the expected life.

Oxygen Sensors:

TO2-1x PPM Oxygen Sensor: Trace Analysis, Standard
 TO2-2x PPM Oxygen Sensor: Trace Analysis, Acidic
 PO2-160 Percent Oxygen Sensor: Percent Analysis, Standard
 PO2-24 Percent Oxygen Sensor: Percent Analysis, Acidic

Oxygen sensors should be periodically calibrated. Factory recommendation is every 2 - 3 months or as the application dictates. Sensors offer excellent linearity with an air calibration, or calibrate to a certified span gas to maximize accuracy.

Order Information:

Record Part Number with selected options in Blank Indicated Area of Form

Model Number:

EMD-482 Oxygen Transmitter

Optional Display:

- D Local Display with Backlight
- X No Display, Blind

Area of Analyzers

- T Trace Analysis
- P Percent Analysis

Optional Sensor:

- 1 Trace Analysis Standard (TO2-1x): 0 - 10ppm, 0 - 100ppm, 0 - 1000ppm, 0 - 1%, 0 - 25%
- 2 Trace Analysis Acidic (TO2-2x): 0 - 10ppm, 0 - 100ppm, 0 - 1000ppm, 0 - 1%, 0 - 25%
- 5 Percent Analysis Standard (PO2-160): 0 - 1%, 0 - 5%, 0 - 10%, 0 - 25%, 0 - 100%
- 6 Percent Analysis Acidic (PO2-24): 0 - 1%, 0 - 5%, 0 - 10%, 0 - 25%, 0 - 100%

Optional Sensor Housing:

- 8 H3 Flow Through with 1/8" Compression Tube Fittings
- 4 H3 Flow Through with 1/4" Compression Tube Fittings
- 6 H3 Flow Through with 6mm Compression Tube Fittings
- K H1 KF-40 Sensor Housing (ideal for Ambient Monitoring or Glove Box Applications)

Optional Factory Pre-Set 2nd Range:

If you want the factory to pre-set a 2nd range, please list the value here:
 | (i.e. 0 - 10ppm, 0 - 100ppm, 0 - 10%, etc.)

Use This Part Number When Ordering

** For assistance when ordering, contact our inside sales specialist **

EMD-482 - - - - -